



SAFETY DATA SHEET

SECTION 1: Product and Company Identification

Product Name: NEW RAPID TAP
Recommended Use: Multi-purpose metal cutting oil

Manufacturer Information:

Relton Corporation-Chemical Division
317 Rolyn Place
Arcadia, CA 91007-2838

Phone: (800)-423-1505
Emergency Number (24 hours):
CHEMTREC 800-424-9300

SECTION 2: Hazards Identification

GHS Classification: Hazardous to the aquatic environment, acute hazard: Category 1, H400
Hazardous to the aquatic environment, long term hazard: Category 1, H410

GHS Label Elements:



Signal Word: Warning

Hazard Statements:

H400 Very toxic to aquatic life
H410 Very toxic to aquatic life with long lasting effects

Precautionary Statements

P201 Obtain special instructions before use.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P308+P313 IF exposed or concerned: Get medical advice/ attention.
P273 Avoid release to the environment.
P391 Collect spillage.
P501 Dispose of contents/container to an appropriate waste treatment facility.

Hazards not otherwise classified (HNOC): Not listed

SECTION 3: Composition/Information on Ingredients

Chemical Name	CAS#	%	
Severely solvent refined heavy naphthenic distillates, Hydrotreated heavy naphthenic petroleum distillates	64741-96-4, 64742-52-5	40-50	*
Alkanes, C14-C16, Chloro	1372804-76-6	30-40	*
Calcium sulfonate	confidential	5-10	*

The remaining ingredients are classified as non hazardous or are below reportable levels.

*The exact percentage of composition has been withheld as a trade secret

SECTION 4: First Aid Measures

Inhalation:	May cause mild respiratory tract irritation. Remove individual to fresh air. If breathing is difficult give oxygen.
Skin Contact:	Flush the affected area with water for 15 minutes minimum. Remove exposed or contaminated clothing and shoes. Wash contaminated clothing before reuse. Seek medical attention if irritation develops.
Eye Contact:	Remove contact lenses if present. Rinse eyes thoroughly with water for 15 minutes minimum. Seek medical attention if eye irritation develops or persists.
Ingestion:	If conscious give one cup of water or milk if available and transport to a medical facility. Do not give anything by mouth to an unconscious person.
Most important symptoms acute or delayed:	Not available
Recommendations for immediate medical care and special treatment:	Not available

SECTION 5: Fire Fighting Measures

Suitable extinguishing media:	Slightly combustible. Use carbon dioxide, extinguishing powder or foam. Avoid water spray.
Unsuitable extinguishing media:	Not available
Specific hazards arising during fire:	Combustion may generate carbon monoxide, carbon dioxide, hydrogen chloride and oxides of sulfur and calcium
Firefighting equipment:	Firefighters should wear suitable protective equipment
Firefighting instructions:	Evacuate personnel to a safe area. Firefighters should use self contained breathing equipment and protective clothing. Keep containers cool with water spray.

SECTION 6: Accidental Release Measures

Personal Precautions:	Wear appropriate protective equipment and clothing during clean up. Keep unprotected persons away.
Environmental Precautions	Do not allow product to enter sewers, surface or ground waters.
Methods and materials for containment and cleanup:	Contain and recover liquid when possible. Absorb with suitable absorbent and place in a chemical waste container for proper disposal (see Section 13, Disposal Considerations).

SECTION 7: Handling and Storage

Precautions for safe handling:	As with all chemical products, avoid contact and wash thoroughly after handling. Do not eat, drink or smoke while using this product. Use only in well-ventilated areas. Remove contaminated clothing and protective equipment before entering eating areas.
Conditions for safe storage including incompatibilities:	All personnel who handle this product should be trained in its safe handling. Store tightly closed in cool, dry, ventilated area. Keep out of direct sunlight and away from heat and incompatible materials. Avoid contact with acids, oxidizing agents, and caustics.

SECTION 8: Exposure Controls/Personal Protection**Exposure limit values**

Material	CAS#	List	Type	Value
Alkanes, C14-C16, Chloro	1372804-76-6	No data available		
Severely solvent refined heavy naphthenic distillate	64741-96-4	OSHA ACGIH	PEL TLV	5 mg/m3 (TWA 8h) 5 mg/m3 (TWA 8h)
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	OSHA ACGIH	PEL TLV	5 mg/m3 (as oil mist) 5 mg/m3 (as oil mist)

Appropriate Engineering Controls: Provide sufficient mechanical (general/and or local exhaust) ventilation to maintain exposure below exposure guidelines, if applicable, or below levels that cause known, suspected, or adverse effects.

Personal Protective Measures

Eye/face protection: Use chemical goggles or full face shield.

Hand protection: Use chemically-resistant gloves.

Respiratory protection: Not required under normal conditions of use. If airborne concentrations exceed applicable exposure limits, use NIOSH approved respiratory protection.

Thermal hazards: Not available

General hygiene considerations: Handle in accordance with good industrial hygiene and safety practice. Eyewash station and safety shower should be in vicinity of work area.

SECTION 9: Physical and Chemical Properties

Appearance:	Amber colored oily liquid
Odor:	Mild petroleum
Odor threshold:	Not available
pH:	Not applicable
Solubility in water:	Insoluble
Viscosity:	Not available
Specific Gravity @ 70F:	1.04
Melting point:	Not available
Freezing point:	Not available
VOC Content (ASTM E-1868-10):	Less than 10g/L AQMD SUPER COMPLIANT
Initial boiling point and boiling range:	Not available
Flash point:	Not determined
Evaporation rate:	Not available
Flammability (solid, gas):	Not available
Upper/Lower flammability or explosive limits (%)	
Flammability limit-lower:	Not available
Flammability limit-upper:	Not available
Explosive limit-lower:	Not available
Explosive limit-upper:	Not available
Vapor pressure	<0.01 mmHg @ 20°C
Vapor density	Heavier than air
Partition coefficient (octanol:water)	Not available

Auto-ignition temperature Not available
 Decomposition temperature Not available
 Decomposition temperature Not available

SECTION 10: Stability and Reactivity

Reactivity: No reactivity hazards are known.

Chemical Stability: Material is stable under normal conditions of storage and handling.

Possibility of hazardous reactions: No hazardous reactions are known under normal conditions of use.

Conditions to avoid: Keep away from heat, sparks, open flames. Protect from freezing.

Materials to avoid: Do not store with strong oxidizing agents. Keep away from heat, sparks, open flames, or all sources of ignition.

Hazardous decomposition products: May include carbon monoxide, carbon dioxide, hydrogen chloride, oxides of calcium and sulfur.

SECTION 11: Toxicological Information

Acute Toxicity:
 C14-C16 chlorinated paraffins
 1372804-76-6

Test	Species	Test Results
Dermal Acute Liquid DNEL	Human	0.0065 mg/kg, 8 hours
Oral Liquid	Rat	23 mg/kg, 90 days by body weight - effected organ kidney; repeat dose study
Inhalation Chronic Liquid DNEL	Rat	6.7 mg/m ³
Oral LD50 Liquid	Rodent	LD50 15000 mg/kg
NOAEL	Rat	100 mg/kg, 90 days by body weight - target organ liver; Reproductive 1-generation study

Skin: Not expected to be a primary skin irritant. Prolonged or repeated contact may cause irritation.

Eyes: May cause mild eye irritation.

Inhalation: May cause mild irritation of the respiratory tract with prolonged exposure.

Ingestion: Ingestion may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea, and abdominal pain.

Delayed and immediate effects of exposure: Not available.

Classification	Category	Hazard Description
Acute toxicity (oral)	Not classified	Not applicable
Acute toxicity (dermal)	Not classified	Not applicable
Acute toxicity (inhalation)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
STOT -single exposure	Not classified	Not applicable
STOT-repeated exposure	Not classified	Not applicable
Serious eye damage/eye irritation	Not classified	Not applicable
Respiratory sensitization	Not classified	Not applicable
Skin sensitization	Not classified	Not applicable
Carcinogenicity	Not classified	Not applicable
Reproductive toxicity	For C14-C16 chlorinated paraffins 1372804-76-6: 400 mg/kg/day diet produced internal hemorrhaging due to the inhibition of vitamin K uptake in rat dams and rat pups. The mode of action for the effect is likely due to a pre-existing vitamin K deficiency in the rodents. This result was not observed in the uterine lining of the rat dams where there was sufficient supply of vitamin K. In addition, the mode of action for the observed effects in rats is not equivalent to human exposure. IRDC (International Research and Development Corporation). 1985. Chlorinated Paraffin: Reproduction Range-Finding Study in Rats. IRDC Report No. 438/049, Mattawan Michigan USA.	

Carcinogenicity:

IARC: No ingredient is considered to be carcinogenic.
OSHA: No ingredient is considered to be carcinogenic.
NTP: No ingredient is considered to be carcinogenic.

SECTION 12: Ecological Information

Ecotoxicity: Alkane C14-C16 Chloro (CAS # 1372804-76-6) is very toxic to aquatic life with long lasting effects

Ingredient	CAS No.	Algae	Fish	Crustacea
Alkanes, C14-C16, Chloro	1372804-76-6	Not listed	LC Bluegill (<i>Lepomis macrochirus</i>) > 0.1 mg/l, 96 hours Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>) > 0.1 mg/l, 96 Hours	Not listed Not listed
severely solvent refined heavy naphthenic distillate 64741-96-4	64741-96-4	Not listed	5000: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50	1000: 48 h <i>Daphnia magna</i> mg/L EC50
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5	64742-52-5	Not listed	5000: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50	1000: 48 h <i>Daphnia magna</i> mg/L EC50

Bioaccumulation potential: Not available.

Mobility: Not available.

Other adverse effects: This material is expected to have adverse effects on marine and plant life. Spills may contaminate drinking water.

SECTION 13: Disposal Considerations

Disposal instructions: Waste disposal must be in accordance with appropriate US Federal, State and Local regulations.

Disposal of contaminated containers or packaging: Dispose of as unused product.

SECTION 14: Transportation Information

DOT
Not regulated as dangerous goods

IATA
Not regulated as dangerous goods

IMDG

UN Number: 3082

UN proper shipping name: Environmentally hazardous substances, liquid, N.O.S, (Alkanes, C14-C16, chloro)

Transport hazard class: 9

Subsidiary risk -

Packing group: III

Labels: 9

Marine Pollutant: Yes

SECTION 15: Regulatory Information

Toxic Substances Control Act (TSCA): All components of this product are on the TSCA Inventory or are exempt from reporting requirements.

SARA 302 Extremely Hazardous Substances: No

SARA 311/312 Classification:

Immediate hazard	No
Delayed hazard	No
Fire hazard	No
Reactive hazard	No
Pressure hazard	No

SARA 313 Components: No

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm

HMIS Information:

Health	1
Flammability	1
Reactivity	0
Personal Protection	B

NFPA Information:



SECTION 16: Other Information

Issue date: March 30, 2015
Revision date: June 19, 2018
Version: 7.0

Disclaimer: Relton Corporation products are manufactured for professional and industrial use only. Relton Corporation believes the information contained herein is valid and accurate and makes no representation or warranty, express or implied, including the warranties of merchantability and fitness, for a particular purpose with respect to the information contained herein.