

Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Revision Date: 07/14/2022	Print Date: 07/25/2022
SECTION 1. IDENTIFICATION		
Product name	: Valvoline™ Full Synthetic SAE 75W-140 Gear O	il
Product code	: 887344	
Manufacturer or supplier's	details	
Company name of supplier	: Valvoline LLC	
Address	: 100 Valvoline Way Lexington, KY 40509 United States of America (USA)	
Telephone	: 1-800-TEAMVAL (1-800-832-6825)	
E-mail address	: SDS@valvoline.com	
Emergency telephone number	: +1-800-VALVOLINE (+1-800-825-8654)	
Recommended use of the o	hemical and restrictions on use	

Recommended use : Engine, gear & lubricating oil.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)			
Eye irritation	:	Category 2A	
Skin sensitisation	:	Category 1	
GHS label elements			
Hazard pictograms	:		
Signal word	:	Warning	



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

ersion: 1.7	Revision Date: 07/14/2022	Print Date: 07/25/2022
Hazard statements	: H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.	
Precautionary statements	 Prevention: P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing must not be allo the workplace. P280 Wear protective gloves/ eye protection/ face 	
	Response: P302 + P352 IF ON SKIN: Wash with plenty of so P305 + P351 + P338 IF IN EYES: Rinse cautiousl for several minutes. Remove contact lenses, if pre- to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get n attention. P337 + P313 If eye irritation persists: Get medical attention. P363 Wash contaminated clothing before reuse.	y with water sent and easy nedical advice/
Other hazards	Disposal: P501 Dispose of contents/ container to an approved disposal plant.	ed waste

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
HYDROTREATED LIGHT	64742-55-8	>= 15 - < 20
PARAFFINIC DISTILLATE		
OLEFINSULFIDE	68937-96-2	>= 1.5 - < 5
Mineral Oil	Not Assigned	>= 1.5 - < 5
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	>= 1.5 - < 5
Reaction products of 4-methyl-2- pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl	Not Assigned	>= 1.5 - < 5



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Revision Date: 07/14/2022	Print Date: 07/25/2022

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	:	May cause an allergic skin reaction. Causes serious eye irritation. No symptoms known or expected.
Notes to physician	:	No hazards which require special first aid measures.
		Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion	:	carbon dioxide and carbon monoxide



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Revision Date: 07/14/2022	Print Date: 07/25/2022
products		
Further information	 Collect contaminated fire extinguishing water separal must not be discharged into drains. Fire residues and contaminated fire extinguishing wa be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be sto separately in closed containments. Use a water spray to cool fully closed containers. 	ater must
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighti necessary.	ing if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8.



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Revision Date: 07/14/2022	Print Date: 07/25/2022
	Smoking, eating and drinking should be prohibited i application area. Take precautionary measures against static dischar Provide sufficient air exchange and/or exhaust in we Open drum carefully as content may be under press Dispose of rinse water in accordance with local and regulations. Persons susceptible to skin sensitisation problems allergies, chronic or recurrent respiratory disease sh be employed in any process in which this mixture is used.	rges. ork rooms. sure. national or asthma, nould not
Conditions for safe storage	 No smoking. Keep container tightly closed in a dry and well-ventiplace. Containers which are opened must be carefully reservent upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comthe technological safety standards. 	ealed and
Further information on storage stability	: No decomposition if stored and applied as directed.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Revision Date: 07/14/2022		Print Date: 07/25/2022
		conditions of use.	
		No personal respiratory protective equipment norma required.	lly
Hand protection			
Remarks	:	The suitability for a specific workplace should be dis- with the producers of the protective gloves.	cussed
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal proproblems.	ocessing
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the wo	
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workda	ay.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	288.5 °F / 142.5 °C Method: Pensky-Martens closed cup
Self-ignition	:	No data available



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Re	vision Date: 07/14/2022	Print Date: 07/25/2022
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	> 1 AIR=1	
Relative density	:	No data available	
Density	:	ca. 0.8603 g/cm3 (60.1 °F / 15.6 °C)	
Solubility(ies) Water solubility	:	insoluble	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	171 mm2/s (104 °F / 40 °C)	
Oxidizing properties	:	No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Hazardous decomposition products	:	No hazardous decomposition products are known.



Version: 1.7

SAFETY DATA SHEET

Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Print Date: 07/25/2022

TION 11. TOXICOLOGIC	AL INFORMATION
Acute toxicity	
Not classified based on a	vailable information.
Product:	
Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Components:	
OLEFINSULFIDE:	
Acute oral toxicity	 LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 401 Assessment: The substance or mixture has no acute oral toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	 LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity Remarks: No mortality observed at this dose.
DISTILLATES (PETROLI	EUM), HYDROTREATED HEAVY PARAFFINIC:
Acute oral toxicity	: LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg
	ethyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterifie xide, and salted by amines, C12-14-tert-alkyl:
Acute oral toxicity	 LD50 (Rat): ca. 2,000 mg/kg Method: OECD Test Guideline 401 Assessment: The component/mixture is moderately toxic after single ingestion.
Skin corrosion/irritation	
Not classified based on a	vailable information.
Product:	
Remarks	: May cause skin irritation and/or dermatitis.

Revision Date: 07/14/2022

Components:

OLEFINSULFIDE:

Result



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

sion: 1.7	Revision Date: 07/14/2022	Print E 07/25/2
DISTILLATES (PETRO	OLEUM), HYDROTREATED HEAVY PARAFFINIC:	
Assessment Result	Slight, transient irritationSlight, transient irritation	
Serious eye damage/ Causes serious eye irr	-	
Product:		
Remarks	: May cause irreversible eye damage.	
<u>Components:</u>		
OLEFINSULFIDE:		
Result	: Slight, transient irritation	
DISTILLATES (PETRO	OLEUM), HYDROTREATED HEAVY PARAFFINIC:	
Result	: No eye irritation	
Assessment	: No eye irritation	
	I-methyl-2-pentanol and diphosphorus pentasulfide, prop ntaoxide, and salted by amines, C12-14-tert-alkyl:	oxylated, esterifi
Result	: Corrosive	
Respiratory or skin s	ensitisation	
Respiratory or skin s Skin sensitisation May cause an allergic		
Skin sensitisation	skin reaction.	
Skin sensitisation May cause an allergic Respiratory sensitisa	skin reaction.	
Skin sensitisation May cause an allergic Respiratory sensitisa	skin reaction. ation	
Skin sensitisation May cause an allergic Respiratory sensitisa Not classified based or	skin reaction. ation	
Skin sensitisation May cause an allergic Respiratory sensitisa Not classified based or <u>Product:</u>	skin reaction. ation n available information.	
Skin sensitisation May cause an allergic Respiratory sensitisa Not classified based or <u>Product:</u> Remarks	skin reaction. ation n available information.	
Skin sensitisation May cause an allergic Respiratory sensitisa Not classified based or <u>Product:</u> Remarks <u>Components:</u> OLEFINSULFIDE: Test Type	skin reaction. ation n available information. : Causes sensitisation. : Maximisation Test	
Skin sensitisation May cause an allergic Respiratory sensitisa Not classified based or <u>Product:</u> Remarks <u>Components:</u> OLEFINSULFIDE: Test Type Species	skin reaction. ation n available information. : Causes sensitisation. : Maximisation Test : Guinea pig	- 40
Skin sensitisation May cause an allergic Respiratory sensitisa Not classified based or <u>Product:</u> Remarks Components: OLEFINSULFIDE: Test Type Species Assessment	skin reaction. ation n available information. : Causes sensitisation. : Maximisation Test : Guinea pig : The product is a skin sensitiser, sub-categor	y 1B.
Skin sensitisation May cause an allergic Respiratory sensitisa Not classified based or <u>Product:</u> Remarks <u>Components:</u> OLEFINSULFIDE: Test Type Species	skin reaction. ation n available information. : Causes sensitisation. : Maximisation Test : Guinea pig	y 1B.



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

sion: 1.7		Re	evision Date: 07/14/2022	Print Date 07/25/202
			pentanol and diphosphorus pentasulfide, propox nd salted by amines, C12-14-tert-alkyl:	ylated, esterified
Assessment		:	The product is a skin sensitiser, sub-category	1B.
Germ cell mu				
Not classified		vailable	information.	
<u>Components</u>				
OLEFINSULF				
Genotoxicity i	in vitro	:	Test Type: in vitro assay Result: Positive results were obtained in some	in vitro tests.
Genotoxicity i	in vivo	:	Test Type: Micronucleus test	
			Species: Mouse Cell type: Bone marrow	
			Method: OECD Test Guideline 474	
			Result: negative	
Caroinegonia	oite c		Result: negative	
Carcinogenic	-	vailable		
-	based on av	vailable		
Not classified	based on av			
Not classified	based on av :: ATED LIGHT	PARA	information.	% (Regulation
Not classified Components HYDROTREA Carcinogenici Assessment	based on av :: ATED LIGHT ity -	PARA	information. FFINIC DISTILLATE: Classified based on DMSO extract content < 3	% (Regulation
Not classified Components HYDROTREA Carcinogenici Assessment	based on av TED LIGHT ity - S (PETROLE	PARA	information. FFINIC DISTILLATE: Classified based on DMSO extract content < 3 (EC) 1272/2008, Annex VI, Part 3, Note L) HYDROTREATED HEAVY PARAFFINIC:	
Not classified <u>Components</u> HYDROTREA Carcinogenici Assessment DISTILLATES Carcinogenici	based on av ATED LIGHT ity - S (PETROLE ity - No compo	EUM), H	information. FFINIC DISTILLATE: Classified based on DMSO extract content < 3 (EC) 1272/2008, Annex VI, Part 3, Note L) HYDROTREATED HEAVY PARAFFINIC: Classified based on DMSO extract content < 3	% (Regulation qual to 0.1% is
Not classified <u>Components</u> HYDROTREA Carcinogenici Assessment DISTILLATES Carcinogenici Assessment	based on av ATED LIGHT ity - S (PETROLE ity - No compo identified a No compo	PARA : EUM), H : onent of as prob	information. FFINIC DISTILLATE: Classified based on DMSO extract content < 3 (EC) 1272/2008, Annex VI, Part 3, Note L) HYDROTREATED HEAVY PARAFFINIC: Classified based on DMSO extract content < 3 (EC) 1272/2008, Annex VI, Part 3, Note L) f this product present at levels greater than or equation	% (Regulation Jual to 0.1% is by IARC.

STOT - single exposure

Not classified based on available information.



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7

Revision Date: 07/14/2022

Print Date: 07/25/2022

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Mineral Oil:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

Further information

Product:

Remarks

: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment		
Acute aquatic toxicity	:	Not classified b

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Chronic aquatic toxicity Category 4; May cause long lasting

harmful effects to aquatic life.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment		
Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

OLEFINSULFIDE:

Ecotoxicology Assessment

Acute aquatic toxicity	:	Harmful to aquatic life.
------------------------	---	--------------------------

Acute aquatic toxicity Category 3; Harmful to aquatic life.



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Re	evision Date: 07/14/2022	Print Date: 07/25/2022					
Chronic aquatic toxicity	:							
		Chronic aquatic toxicity Category 3; Harmful to aqua with long lasting effects.	atic life					
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:								
Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h						
Toxicity to daphnia and other aquatic invertebrates	r :	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h						
Toxicity to algae/aquatic plants	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h						
Toxicity to fish (Chronic toxicity)	:	NOEC (Fish): 10 mg/l						
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	r :	NOEC (Aquatic invertebrates): 10 mg/l						
Ecotoxicology Assessmen	t							
Acute aquatic toxicity	:	Not classified based on available information.						
Chronic aquatic toxicity	:	Not classified based on available information.						
		pentanol and diphosphorus pentasulfide, propoxylate nd salted by amines, C12-14-tert-alkyl:	d, esterified					
Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 Exposure time: 96 h Test Type: static test Test substance: WAF	1 mg/l					
		Method: OECD Test Guideline 203						
Toxicity to daphnia and other aquatic invertebrates	r :	EL50 (Daphnia magna (Water flea)): ca. 91.4 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF						
		Method: OECD Test Guideline 202						
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green alga mg/l End point: Growth inhibition Exposure time: 96 h Test Type: static test	ae)): 15					
		Method: OECD Test Guideline 201						



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

NOEC (Pseudokirchneriella subcapitata (green algar mg/l End point: Growth inhibition Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 201 NOEC (Daphnia magna (Water flea)): 0.12 mg/l End point: Reproduction Test Exposure time: 21 d Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211 Toxic to aquatic life. Toxic to aquatic life with long lasting effects.	e)): 3.3
End point: Reproduction Test Exposure time: 21 d Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211 Toxic to aquatic life.	
Toxic to aquatic life with long lasting effects.	
Result: Not readily biodegradable. Biodegradation: 13 % Exposure time: 28 d Method: OECD Test Guideline 301B	
entanol and diphosphorus pentasulfide, propoxylated d salted by amines, C12-14-tert-alkyl:	d, esterif
Result: Not readily biodegradable. Biodegradation: 7.4 % Exposure time: 28 d Method: Modified Sturm Test	
YDROTREATED HEAVY PARAFFINIC: log Pow: Expected > 7	
	Exposure time: 28 d Method: OECD Test Guideline 301B entanol and diphosphorus pentasulfide, propoxylated I salted by amines, C12-14-tert-alkyl: Result: Not readily biodegradable. Biodegradation: 7.4 % Exposure time: 28 d Method: Modified Sturm Test



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Revision Date: 07/14/2022	Print Date: 07/25/2022
Partition coefficient: n- octanol/water	: Remarks: No data available	
Mobility in soil No data available Other adverse effects		
Product:		
Ozone-Depletion Potential	 Regulation: 40 CFR Protection of Environment; Part Protection of Stratospheric Ozone - CAA Section 60: Substances Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defir U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A B). 	2 Class I ned by the
Additional ecological information	: An environmental hazard cannot be excluded in the unprofessional handling or disposal. May cause long lasting harmful effects to aquatic life	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG Not regulated as a dangerous good

IATA-DGR Not regulated as a dangerous good

IMDG-Code



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7

Revision Date: 07/14/2022

Print Date: 07/25/2022

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.		Calculated product RQ
		(lbs)	(lbs)
METHANOL	67-56-1	100	100 (F003)
ETHYL BENZENE	100-41-4	100	100 (F003)
METHYL ISOBUTYL KETONE	108-10-1	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, or solids) Respiratory or skin sensitisation Serious eye damage or eye irritation
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

sion: 1.7	Revision Date: 07/14/2022	Print Date 07/25/2022
Clean Water Act		
The following Hazard Table 116.4A:	ous Substances are listed under the U	.S. CleanWater Act, Section 311,
ETHYL BE	NZENE 100-41-4	>= 0 - < 0.1 %
NAPHTHA		>= 0 - < 0.1 %
The following Hazard 117.3:	ous Chemicals are listed under the U.S	S. CleanWater Act, Section 311, Table
ETHYL BE		>= 0 - < 0.1 %
NAPHTHA		>= 0 - < 0.1 %
307	t contain any toxic pollutants listed und	
This product does no	t contain any priority pollutants related	to the U.S. Clean Water Act
US State Regulation	IS	
Massachusetts Righ		
HYDROTE	REATED LIGHT PARAFFINIC DISTILL	ATE 64742-55-8
Pennsylvania Right	To Know	
	NE/ETHYLENE COPOLYMER	9010-79-1
	ENE TRIMER, HYDROGENATED	151006-62-1
	ENE, HOMOPOLYMER, HYDROGENA CARBOXYLATE	ATED 151006-63-2 Not Assigned
OLEFINSU		68937-96-2
Mineral Oil		Not Assigned
DISTILLAT PARAFFIN	ES (PETROLEUM), HYDROTREATEI	
Maine Chemicals of	High Concern	
Lubricating based	oils (petroleum), C15-30, hydrotreated	d neutral oil- 72623-86-0
ETHYL BE	NZENE	100-41-4
NAPHTHA	LENE	91-20-3
Vermont Chemicals	•	
Lubricating based	oils (petroleum), C15-30, hydrotreated	d neutral oil- 72623-86-0
ETHYL BE	NZENE	100-41-4
NAPHTHA	LENE	91-20-3
-	cals of High Concern	
Lubricating based	oils (petroleum), C15-30, hydrotreated	d neutral oil- 72623-86-0
ETHYL BE	NZENE	100-41-4
NAPHTHA		91-20-3

WARNING: This product can expose you to chemicals including HYDROTREATED LIGHT PARAFFINIC DISTILLATE, DISTILLATES (PETROLEUM), HYDROTREATED HEAVY



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7	Re	evision Date: 07/14/2022	Print Date: 07/25/2022
	IIC, which is/are knowr P65Warnings.ca.gov.	n to the State of California to cause cancer. For more	information
l		bstances HT PARAFFINIC DISTILLATE 64742-55- DLEUM), HYDROTREATED HEAVY 64742-54-	
I	•	e Limits for Chemical Contaminants DLEUM), HYDROTREATED HEAVY 64742-54-	7
The comp	onents of this produc	t are reported in the following inventories:	
TCSI	:	On the inventory, or in compliance with the invento	ry
TSCA	:	All substances listed as active on the TSCA inventor	ory
AIIC	:	Not in compliance with the inventory	
DSL	:	All components of this product are on the Canadian	າ DSL
ENCS	:	On the inventory, or in compliance with the invento	ry
ISHL	:	Not in compliance with the inventory	
KECI	:	On the inventory, or in compliance with the invento	ry
PICCS	:	On the inventory, or in compliance with the invento	ry
IECSC	:	On the inventory, or in compliance with the invento	ry
NZIoC	:	Not in compliance with the inventory	
TECI	:	Not in compliance with the inventory	

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil


Version: 1.7

Revision Date: 07/14/2022

Print Date: 07/25/2022







Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1
		Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate;



Valvoline™ Full Synthetic SAE 75W-140 Gear Oil

Version: 1.7

Revision Date: 07/14/2022

Print Date: 07/25/2022

NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date

: 07/14/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0388288