

64-020

# SPEED SHORE®

PIONEERING TRENCH SAFETY

## TABULATED DATA AND STACK TUBE CERTIFICATION

SERIAL NUMBER: 0-2379		MODEL: TS-0816TL4
HEIGHT = 8 feet	LENGTH = 16 feet	THICKNESS = 4 inches
MAXIMUM LATERAL EARTH PRESSURE = 975 pounds per square foot		

MAXIMUM DEPTH OF EXCAVATION		
O.S.H.A. Soil Type	Equivalent Weight Effect (p.c.f.)	Depth "H" (feet)
A	25	40
B	45	24
C	60	19
C	80	15
Spreader Size = 5 inch Schedule 80 Pipe / Maximum Spreader Length = 12 feet		

This shield is manufactured to meet the requirements of O.S.H.A. CFR 29, Part 1926, Subpart P. This shield must be used in a manner consistent with safe working procedures, Federal, State and local regulation and manufacturer's instructions. Contact manufacturer for any non-standard use of this trench shield.

### GENERAL NOTES AND INSTRUCTIONS:

- Contractors must assign a "competent person", knowledgeable and capable of complying with all federal regulations, state and local laws and ordinances. **NOTE:** For copies of applicable federal or state laws contact: Dept. of Labor, Occupational Safety and Health Division.
- A "competent person", trained and experienced in the proper use of trench shields, safe excavation practices and soil classification methods must direct and control the use of this trench shield.
- This Tabulated Data applies to standard products manufactured exclusively by SPEED SHORE CORPORATION. This data complies with the requirements of federal O.S.H.A. CFR 29, Part 1926, Subpart P-Excavations. Information not found in this data shall be referenced by obtaining copies of the applicable Federal or State laws governing excavation.
- Modifications of this product shall be in writing and shall accompany this Tabulated Data sheet. Any modification not specifically allowed by SPEED SHORE CORPORATION voids this data.

11.01.96R

Page 1 of 1

### SPEED SHORE CORPORATION

P.O. Box 262591  
Houston, Texas 77207-2591  
Phone (713) 943-0750 Fax (713) 943-8483

