

64-028

SPEED SHORE® PIONEERING TRENCH SAFETY

TABULATED DATA AND STACK TUBE CERTIFICATION

SERIAL NUMBER:	0-2421	MODEL: TS-0810TL3
HEIGHT = 8 feet	LENGTH = 10 feet	THICKNESS = 3 inches
MAXIMUM LATERAL EARTH PRESSURE = 1210 pounds per square foot		

MAXIMUM DEPTH OF EXCAVATION		
O.S.H.A. Soil Type	Equivalent Weight Effect (p.s.f.)	Depth "H" (feet)
A	25	50
B	45	29
C	60	23
C	80	18
Spreader Size = 5 inch Schedule 80 Pipe / Maximum Spreader Length = 12 feet		

This shield is manufactured to meet the requirements of O.S.H.A. CFR 29, Part 1926, Subpart P. This shield must be used in a manner consistent with safe working procedures, Federal, State and local regulation and manufacturer's instructions. Contact manufacturer for any non-standard use of this trench shield.

GENERAL NOTES AND INSTRUCTIONS:

- Contractors must assign a "competent person", knowledgeable and capable of complying with all federal regulations, state and local laws and ordinances. NOTE: For copies of applicable federal or state laws contact: Dept. of Labor, Occupational Safety and Health Division.
- A "competent person", trained and experienced in the proper use of trench shields, safe excavation practices and soil classification methods must direct and control the use of this trench shield.
- This Tabulated Data applies to standard products manufactured exclusively by SPEED SHORE CORPORATION. This data complies with the requirements of federal O.S.H.A. CFR 29, Part 1926, Subpart P-Excavations. Information not found in this data shall be referenced by obtaining copies of the applicable Federal or State laws governing excavation.
- Modifications of this product shall be in writing and shall accompany this Tabulated Data sheet. Any modification not specifically allowed by SPEED SHORE CORPORATION voids this data.

11.01.96R

Page 1 of 1

SPEED SHORE CORPORATION

3330 S. Sam Houston Parkway E.
Houston, Texas 77047
Phone (713) 943-0750 Fax (713) 943-8483

